

Package ‘chipenrich.data’

September 17, 2024

Title Companion package to chipenrich

Version 2.28.0

Date 2023-03-29

Description Supporting data for the chipenrich package. Includes pre-defined gene sets, gene locus definitions, and mappability estimates.

biocViews ChIPSeq, Epigenetics, FunctionalGenomics, GeneSetEnrichment, HistoneModification, Regression

Depends R (>= 3.4.0)

Imports AnnotationDbi, BiocGenerics, methods, GenomicRanges, GenomeInfoDb, IRanges, readr, rtracklayer, S4Vectors, utils

License GPL-3

Encoding UTF-8

LazyData true

Suggests BiocStyle, devtools, knitr, rmarkdown, roxygen2, testthat, GO.db, org.Dm.eg.db, org.Dr.eg.db, org.Hs.eg.db, org.Mm.eg.db, org.Rn.eg.db, TxDb.Dmelanogaster.UCSC.dm3.ensGene, TxDb.Dmelanogaster.UCSC.dm6.ensGene, TxDb.Drerio.UCSC.danRer10.refGene, TxDb.Hsapiens.UCSC.hg19.knownGene, TxDb.Hsapiens.UCSC.hg38.knownGene, TxDb.Mmusculus.UCSC.mm9.knownGene, TxDb.Mmusculus.UCSC.mm10.knownGene, TxDb.Rnorvegicus.UCSC.rn4.ensGene, TxDb.Rnorvegicus.UCSC.rn5.refGene, TxDb.Rnorvegicus.UCSC.rn6.refGene

VignetteBuilder knitr

RoxygenNote 6.1.1

Maintainer Kai Wang <wangdaha@umich.edu>

git_url <https://git.bioconductor.org/packages/chipenrich.data>

git_branch RELEASE_3_19

git_last_commit 70d7917

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-09-17

Author Ryan P. Welch [aut, cph],
Chee Lee [aut],
Raymond G. Cavalcante [aut],
Kai Wang [cre],
Laura J. Scott [ths],
Maureen A. Sartor [ths]

Contents

chipenrich.data	8
enhancer.dnase_thurman.0	8
gene.enh.desc	9
GeneSet-class	9
geneset.biocarta_pathway.hsa	10
geneset.biocarta_pathway.mmu	11
geneset.biocarta_pathway.rno	11
geneset.ctd.hsa	12
geneset.ctd.mmu	12
geneset.cytoband.hsa	13
geneset.drug_bank.hsa	14
geneset.drug_bank.mmu	14
geneset.drug_bank.rno	15
geneset.GOBP.dme	15
geneset.GOBP.dre	16
geneset.GOBP.hsa	17
geneset.GOBP.mmu	17
geneset.GOBP.rno	18
geneset.GOCC.dme	19
geneset.GOCC.dre	19
geneset.GOCC.hsa	20
geneset.GOCC.mmu	21
geneset.GOCC.rno	21
geneset.GOMF.dme	22
geneset.GOMF.dre	23
geneset.GOMF.hsa	23
geneset.GOMF.mmu	24
geneset.GOMF.rno	25
geneset.hallmark.hsa	25
geneset.immunologic.hsa	26
geneset.kegg_pathway.hsa	27
geneset.kegg_pathway.mmu	28
geneset.kegg_pathway.rno	28
geneset.mesh.hsa	29
geneset.mesh.mmu	29

locusdef.dm6.10kb_outside 62

locusdef.dm6.10kb_outside_upstream 63

locusdef.dm6.1kb 64

locusdef.dm6.1kb_outside 65

locusdef.dm6.1kb_outside_upstream 65

locusdef.dm6.5kb 66

locusdef.dm6.5kb_outside 67

locusdef.dm6.5kb_outside_upstream 68

locusdef.dm6.exon 68

locusdef.dm6.intron 69

locusdef.dm6.nearest_gene 70

locusdef.dm6.nearest_tss 71

locusdef.hg19.10kb 71

locusdef.hg19.10kb_outside 72

locusdef.hg19.10kb_outside_upstream 73

locusdef.hg19.1kb 74

locusdef.hg19.1kb_outside 74

locusdef.hg19.1kb_outside_upstream 75

locusdef.hg19.5kb 76

locusdef.hg19.5kb_outside 77

locusdef.hg19.5kb_outside_upstream 77

locusdef.hg19.exon 78

locusdef.hg19.intron 79

locusdef.hg19.nearest_gene 80

locusdef.hg19.nearest_tss 80

locusdef.hg38.10kb 81

locusdef.hg38.10kb_outside 82

locusdef.hg38.10kb_outside_upstream 83

locusdef.hg38.1kb 83

locusdef.hg38.1kb_outside 84

locusdef.hg38.1kb_outside_upstream 85

locusdef.hg38.5kb 86

locusdef.hg38.5kb_outside 86

locusdef.hg38.5kb_outside_upstream 87

locusdef.hg38.exon 88

locusdef.hg38.intron 89

locusdef.hg38.nearest_gene 89

locusdef.hg38.nearest_tss 90

locusdef.mm10.10kb 91

locusdef.mm10.10kb_outside 92

locusdef.mm10.10kb_outside_upstream 92

locusdef.mm10.1kb 93

locusdef.mm10.1kb_outside 94

locusdef.mm10.1kb_outside_upstream 95

locusdef.mm10.5kb 95

locusdef.mm10.5kb_outside 96

locusdef.mm10.5kb_outside_upstream 97

locusdef.mm10.exon 98

mappa.hg19.nearest_tss.50mer 166
mappa.hg19.nearest_tss.75mer 167
mappa.mm9.10kb.100mer 168
mappa.mm9.10kb.36mer 168
mappa.mm9.10kb.40mer 169
mappa.mm9.10kb.50mer 170
mappa.mm9.10kb.75mer 170
mappa.mm9.1kb.100mer 171
mappa.mm9.1kb.36mer 172
mappa.mm9.1kb.40mer 172
mappa.mm9.1kb.50mer 173
mappa.mm9.1kb.75mer 174
mappa.mm9.5kb.100mer 174
mappa.mm9.5kb.36mer 175
mappa.mm9.5kb.40mer 176
mappa.mm9.5kb.50mer 176
mappa.mm9.5kb.75mer 177
mappa.mm9.exon.100mer 178
mappa.mm9.exon.36mer 178
mappa.mm9.exon.40mer 179
mappa.mm9.exon.50mer 180
mappa.mm9.exon.75mer 180
mappa.mm9.intron.100mer 181
mappa.mm9.intron.36mer 182
mappa.mm9.intron.40mer 182
mappa.mm9.intron.50mer 183
mappa.mm9.intron.75mer 184
mappa.mm9.nearest_gene.100mer 184
mappa.mm9.nearest_gene.36mer 185
mappa.mm9.nearest_gene.40mer 186
mappa.mm9.nearest_gene.50mer 186
mappa.mm9.nearest_gene.75mer 187
mappa.mm9.nearest_tss.100mer 188
mappa.mm9.nearest_tss.36mer 188
mappa.mm9.nearest_tss.40mer 189
mappa.mm9.nearest_tss.50mer 190
mappa.mm9.nearest_tss.75mer 190
peaks_E2F4 191
peaks_H3K4me3_GM12878 192
spline.log_dtss.90ENCODE 192
tss.danRer10 193
tss.dm3 193
tss.dm6 194
tss.hg19 194
tss.hg38 195
tss.mm10 195
tss.mm9 196
tss.rn4 197

tss.rn5	197
tss.rn6	198

Index	199
--------------	------------

chipenrich.data	<i>chipenrich.data: Data for chipenrich: gene set enrichment analysis for ChIP-seq data</i>
-----------------	---

Description

Supporting data for the chipenrich package. Includes pre-defined gene sets, gene locus definitions, and mappability estimates.

enhancer.dnase_thurman.0	<i>Enhancer locations</i>
--------------------------	---------------------------

Description

A GRanges with all the enhancer locations for hg19. The locations were found using a combination of DNase data and from Thurman et al (PMID: 22955617)

Usage

```
enhancer.dnase_thurman.0
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

```
geneset.biocarta_pathway.mmu  
geneset.biocarta_pathway.mmu
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.biocarta_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

```
geneset.biocarta_pathway.rno  
geneset.biocarta_pathway.rno
```

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.biocarta_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.drug_bank.rno` *geneset.drug_bank.rno*

Description

GeneSet object which stores information about sets of genes.

These objects are used internally by the `chipenrich` package.

Usage

```
data(geneset.drug_bank.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)

For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.GOBP.dme` *geneset.GOBP.dme genesets for Drosophila melanogaster*

Description

Gene Ontology Biological Process (GOBP) genesets for *Drosophila melanogaster*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:24:38 2017.

Usage

```
geneset.GOBP.dme
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOBP.dre	<i>geneset.GOBP.dre genesets for Danio rerio</i>
------------------	--

Description

Gene Ontology Biological Process (GOBP) genesets for Danio rerio. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:25:08 2017.

Usage

```
geneset.GOBP.dre
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dr.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.dme	<i>geneset.GOCC.dme</i> genesets for <i>Drosophila melanogaster</i>
------------------	---

Description

Gene Ontology Cellular Component (GOCC) genesets for *Drosophila melanogaster*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:24:38 2017.

Usage

geneset.GOCC.dme

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.dre	<i>geneset.GOCC.dre</i> genesets for <i>Danio rerio</i>
------------------	---

Description

Gene Ontology Cellular Component (GOCC) genesets for *Danio rerio*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:25:08 2017.

Usage

geneset.GOCC.dre

geneset.GOCC.mmu *geneset.GOCC.mmu genesets for Mus musculus*

Description

Gene Ontology Cellular Component (GOCC) genesets for *Mus musculus*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:23:23 2017.

Usage

geneset.GOCC.mmu

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Mm.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOCC.rno *geneset.GOCC.rno genesets for Rattus norvegicus*

Description

Gene Ontology Cellular Component (GOCC) genesets for *Rattus norvegicus*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:24:10 2017.

Usage

geneset.GOCC.rno

geneset.GOMF.dre *geneset.GOMF.dre genesets for Danio rerio*

Description

Gene Ontology Molecular Function (GOMF) genesets for Danio rerio. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:25:08 2017.

Usage

geneset.GOMF.dre

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

org.Dr.eg.db_3.4.2 and GO.db_3.4.2

geneset.GOMF.hsa *geneset.GOMF.hsa genesets for Homo sapiens*

Description

Gene Ontology Molecular Function (GOMF) genesets for Homo sapiens. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Oct 16 16:22:22 2017.

Usage

geneset.GOMF.hsa

geneset.GOMF.rno *geneset.GOMF.rno genesets for Rattus norvegicus*

Description

Gene Ontology Molecular Function (GOMF) genesets for *Rattus norvegicus*. All genesets are required to have \geq 10 Entrez IDs. Built on Mon Oct 16 16:24:10 2017.

Usage

```
geneset.GOMF.rno
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. GOBP.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. *Homo sapiens*.

set.gene An environment containing a list whose keys are database specific accessions (e.g. GO IDs for GO terms), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

```
org.Rn.eg.db_3.4.2 and GO.db_3.4.2
```

geneset.hallmark.hsa *geneset.hallmark.hsa genesets for Hallmark (MSigDB)*

Description

Hallmark (MSigDB) (hallmark) genesets. All genesets are required to have \geq 10 Entrez IDs. Built on Mon Oct 16 18:46:15 2017.

Usage

```
geneset.hallmark.hsa
```


geneset.kegg_pathway.mmu
geneset.kegg_pathway.mmu

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.kegg_pathway.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.kegg_pathway.rno
geneset.kegg_pathway.rno

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.kegg_pathway.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.mesh.hsa` *geneset.mesh.hsa*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.mesh.mmu` *geneset.mesh.mmu*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.mesh.rno` *geneset.mesh.rno*

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.mesh.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

`geneset.metabolite.hsa`
geneset.metabolite.hsa

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.hsa)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.metabolite.mmu
geneset.metabolite.mmu

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.mmu)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

geneset.metabolite.rno
geneset.metabolite.rno

Description

GeneSet object which stores information about sets of genes.
These objects are used internally by the chipenrich package.

Usage

```
data(geneset.metabolite.rno)
```

Format

See [GeneSet-class](#) for a description of the format.

See Also

For more information about genesets: [chipenrich.data](#)
For information regarding how the genesets were created: `browseVignettes("chipenrich.data")`

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Source

http://www.reactome.org/download/current/NCBI2Reactome_All_Levels.txt downloaded on 2017-03-19

geneset.reactome.mmu *geneset.reactome.mmu genesets for Mus musculus*

Description

Reactome genesets for *Mus musculus*. All genesets are required to have ≥ 10 Entrez IDs. Built on Mon Mar 20 15:13:55 2017.

Usage

```
geneset.reactome.mmu
```

Format

A GeneSet object with the following slots:

type A character indicating the type of genesets, e.g. Reactome.

dburl A character of the URL of the database underlying the genesets.

organism A character of the organism, e.g. Homo sapiens.

set.gene An environment containing a list whose keys are database specific accessions (e.g. R-HSA-109688), and whose elements are character vectors of Entrez Gene IDs.

all.genes A character vector of all the Entrez Gene IDs contained over all the genesets in this type.

set.name An environment containing a list whose keys are database specific accessions, and whose elements are human readable geneset names.

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and `gene_symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `danRer10`.

organism A character indicating the organism name. In this case, `Danio rerio`.

Details

Built on Fri Apr 13 09:54:26 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

locusdef.danRer10.1kb_outside_upstream

locusdef.danRer10.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.danRer10.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and `gene_symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `danRer10`.

organism A character indicating the organism name. In this case, `Danio rerio`.

Details

Built on Fri Apr 13 09:54:25 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

locusdef.danRer10.5kb *locusdef.danRer10.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.danRer10.5kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, danRer10.

organism A character indicating the organism name. In this case, Danio rerio.

Details

Built on Fri Apr 13 09:54:26 2018.

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

locusdef.danRer10.intron
locusdef.danRer10.intron locus definition

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.danRer10.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `danRer10`.

organism A character indicating the organism name. In this case, `Danio rerio`.

Details

Built on Fri Apr 13 09:54:25 2018.

Source

R packages: `TxDb.Drerio.UCSC.danRer10.refGene_3.4.2` and `org.Dr.eg.db_3.5.0`.

locusdef.danRer10.nearest_gene
locusdef.danRer10.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

```
locusdef.danRer10.nearest_gene
```


Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

`locusdef.dm3.10kb` *locusdef.dm3.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.dm3.10kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm3`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

locusdef.dm3.1kb_outside_upstream

locusdef.dm3.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm3.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm3`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: `TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2` and `org.Dm.eg.db_3.5.0`.

locusdef.dm3.5kb

locusdef.dm3.5kb locus definition

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.dm3.5kb
```


Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

locusdef.dm3.5kb_outside_upstream

locusdef.dm3.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm3.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:05 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

locusdef.dm3.exon	<i>locusdef.dm3.exon locus definition</i>
-------------------	---

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.dm3.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:04 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

locusdef.dm3.intron	<i>locusdef.dm3.intron locus definition</i>
---------------------	---

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.dm3.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:04 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

locusdef.dm3.nearest_gene

locusdef.dm3.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESSs.

Usage

```
locusdef.dm3.nearest_gene
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm3.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:03 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

`locusdef.dm3.nearest_tss`

locusdef.dm3.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.dm3.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm3`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the dm3 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:03 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

<code>locusdef.dm6.1kb</code>	<i>locusdef.dm6.1kb locus definition</i>
-------------------------------	--

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.dm6.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm6`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:34 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

locusdef.dm6.1kb_outside

locusdef.dm6.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.dm6.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm6`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: `TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1` and `org.Dm.eg.db_3.5.0`.

locusdef.dm6.1kb_outside_upstream

locusdef.dm6.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.dm6.1kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm6`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the `dm6` genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:34 2018.

Source

R packages: `TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1` and `org.Dm.eg.db_3.5.0`.

locusdef.dm6.5kb *locusdef.dm6.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.dm6.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm6`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

locusdef.dm6.5kb_outside

locusdef.dm6.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.dm6.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm6`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

locusdef.dm6.5kb_outside_upstream

locusdef.dm6.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.dm6.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm6`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the `dm6` genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:35 2018.

Source

R packages: `TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1` and `org.Dm.eg.db_3.5.0`.

locusdef.dm6.exon

locusdef.dm6.exon locus definition

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.dm6.exon
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:33 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

locusdef.dm6.intron *locusdef.dm6.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.dm6.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, dm6.

organism A character indicating the organism name. In this case, Drosophila melanogaster.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:34 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

locusdef.dm6.nearest_gene

locusdef.dm6.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.dm6.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm6`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the dm6 genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:33 2018.

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

locusdef.dm6.nearest_tss
locusdef.dm6.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

locusdef.dm6.nearest_tss

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `dm6`.

organism A character indicating the organism name. In this case, `Drosophila melanogaster`.

Details

For the `dm6` genome, original gene IDs are from FLYBASE and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:53:33 2018.

Source

R packages: `TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1` and `org.Dm.eg.db_3.5.0`.

locusdef.hg19.10kb *locusdef.hg19.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.hg19.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:58 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata. EntrezG

locusdef.hg19.10kb_outside

locusdef.hg19.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.hg19.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:59 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE
resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation.
and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.EntrezG

locusdef.hg19.10kb_outside_upstream

locusdef.hg19.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.hg19.10kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:58 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE
resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation.
and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.EntrezG

locusdef.hg19.1kb *locusdef.hg19.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.hg19.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:55 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.EntrezG

locusdef.hg19.1kb_outside
locusdef.hg19.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.hg19.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:56 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.EntrezG

locusdef.hg19.1kb_outside_upstream

locusdef.hg19.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.hg19.1kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:56 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE
resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation.
and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.EntrezG

locusdef.hg19.5kb *locusdef.hg19.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.hg19.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:57 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE
resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation.
and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.EntrezG

 locusdef.hg19.5kb_outside

locusdef.hg19.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.hg19.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:58 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata. EntrezG

 locusdef.hg19.5kb_outside_upstream

locusdef.hg19.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.hg19.5kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:57 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.EntrezG

locusdef.hg19.exon *locusdef.hg19.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.hg19.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:53 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE
resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation.
and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.EntrezG

locusdef.hg19.intron *locusdef.hg19.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.hg19.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:55 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE
resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation.
and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.EntrezG

locusdef.hg19.nearest_gene

locusdef.hg19.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.hg19.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:51 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata. EntrezG

locusdef.hg19.nearest_tss

locusdef.hg19.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

locusdef.hg19.nearest_tss

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg19.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:45:51 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata.EntrezG

locusdef.hg38.10kb *locusdef.hg38.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.hg38.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:42 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.10kb_outside

locusdef.hg38.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.hg38.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:43 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.10kb_outside_upstream
locusdef.hg38.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.hg38.10kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:43 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.1kb *locusdef.hg38.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.hg38.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:39 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.1kb_outside

locusdef.hg38.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.hg38.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:40 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/genCODE/Gencode_human/release_25/genCODE.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/genCODE/Gencode_human/release_25/genCODE.v25.metadata.EntrezGene.gz

locusdef.hg38.1kb_outside_upstream

locusdef.hg38.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.hg38.1kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:39 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/genCODE/Gencode_human/release_25/genCODE.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/genCODE/Gencode_human/release_25/genCODE.v25.metadata.EntrezGene.gz

locusdef.hg38.5kb *locusdef.hg38.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.hg38.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:41 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.5kb_outside
locusdef.hg38.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.hg38.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:42 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.5kb_outside_upstream

locusdef.hg38.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.hg38.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:41 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.exon *locusdef.hg38.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.hg38.exon
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:37 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.intron *locusdef.hg38.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.hg38.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:38 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.nearest_gene
locusdef.hg38.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.hg38.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:34 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.hg38.nearest_tss

locusdef.hg38.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

locusdef.hg38.nearest_tss

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, hg38.

organism A character indicating the organism name. In this case, Homo sapiens.

Details

Built on Fri Apr 13 09:49:34 2018.

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata.EntrezGene.gz

locusdef.mm10.10kb *locusdef.mm10.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.mm10.10kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:40 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.10kb_outside

locusdef.mm10.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.mm10.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm10`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Fri Apr 13 09:51:41 2018.

Source

R packages: `TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0` and `org.Mm.eg.db_3.5.0`. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.10kb_outside_upstream

locusdef.mm10.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.mm10.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm10`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Fri Apr 13 09:51:40 2018.

Source

R packages: `TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0` and `org.Mm.eg.db_3.5.0`. GENCODE resources: `ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz` and `ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz`

`locusdef.mm10.1kb` *locusdef.mm10.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.mm10.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm10`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Fri Apr 13 09:51:37 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.1kb_outside

locusdef.mm10.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.mm10.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:38 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.1kb_outside_upstream
locusdef.mm10.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.mm10.1kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:37 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.5kb *locusdef.mm10.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.mm10.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm10`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Fri Apr 13 09:51:38 2018.

Source

R packages: `TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0` and `org.Mm.eg.db_3.5.0`. GENCODE resources: `ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz` and `ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz`

locusdef.mm10.5kb_outside

locusdef.mm10.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.mm10.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm10`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Fri Apr 13 09:51:39 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.5kb_outside_upstream

locusdef.mm10.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.mm10.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:39 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.exon *locusdef.mm10.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.mm10.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:35 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.intron *locusdef.mm10.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.mm10.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:36 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.nearest_gene

locusdef.mm10.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.mm10.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:33 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm10.nearest_tss

locusdef.mm10.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.mm10.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm10.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:51:33 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

locusdef.mm9.10kb *locusdef.mm9.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.mm9.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:44 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.10kb_outside
locusdef.mm9.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.mm9.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:44 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.10kb_outside_upstream

locusdef.mm9.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.mm9.10kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:44 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.1kb *locusdef.mm9.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.mm9.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:41 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.1kb_outside

locusdef.mm9.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.mm9.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm9`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Fri Apr 13 09:50:42 2018.

Source

R packages: `TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2` and `org.Mm.eg.db_3.5.0`. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.1kb_outside_upstream

locusdef.mm9.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.mm9.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm9`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Fri Apr 13 09:50:41 2018.

Source

R packages: `TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2` and `org.Mm.eg.db_3.5.0`. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

`locusdef.mm9.5kb` *locusdef.mm9.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.mm9.5kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm9`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Fri Apr 13 09:50:42 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.5kb_outside

locusdef.mm9.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.mm9.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:43 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.5kb_outside_upstream
locusdef.mm9.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.mm9.5kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm9`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Fri Apr 13 09:50:43 2018.

Source

R packages: `TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2` and `org.Mm.eg.db_3.5.0`. GENCODE resources: `ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz` and `ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz`

locusdef.mm9.exon *locusdef.mm9.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.mm9.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, *Mus musculus*.

Details

Built on Fri Apr 13 09:50:39 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.intron *locusdef.mm9.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.mm9.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, *Mus musculus*.

Details

Built on Fri Apr 13 09:50:41 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.nearest_gene

locusdef.mm9.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.mm9.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, mm9.

organism A character indicating the organism name. In this case, Mus musculus.

Details

Built on Fri Apr 13 09:50:37 2018.

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

locusdef.mm9.nearest_tss

locusdef.mm9.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.mm9.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `mm9`.

organism A character indicating the organism name. In this case, `Mus musculus`.

Details

Built on Fri Apr 13 09:50:37 2018.

Source

R packages: `TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2` and `org.Mm.eg.db_3.5.0`. GENCODE resources: `ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz` and `ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz`

locusdef.rn4.10kb

locusdef.rn4.10kb locus definition

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.rn4.10kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the `rn4` genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:02 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2` and `org.Rn.eg.db_3.5.0`.

locusdef.rn4.10kb_outside

locusdef.rn4.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn4.10kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:03 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

locusdef.rn4.10kb_outside_upstream

locusdef.rn4.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.rn4.10kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:02 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

locusdef.rn4.1kb *locusdef.rn4.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.rn4.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the `rn4` genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:01 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2` and `org.Rn.eg.db_3.5.0`.

locusdef.rn4.1kb_outside *locusdef.rn4.1kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn4.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:01 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

```
locusdef.rn4.1kb_outside_upstream
```

```
locusdef.rn4.1kb_outside_upstream locus definition
```

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn4.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:01 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

locusdef.rn4.5kb	<i>locusdef.rn4.5kb locus definition</i>
------------------	--

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

```
locusdef.rn4.5kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:01 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

locusdef.rn4.5kb_outside

locusdef.rn4.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn4.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the `rn4` genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:02 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2` and `org.Rn.eg.db_3.5.0`.

locusdef.rn4.5kb_outside_upstream

locusdef.rn4.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn4.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the `rn4` genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:02 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2` and `org.Rn.eg.db_3.5.0`.

<code>locusdef.rn4.exon</code>	<i>locusdef.rn4.exon locus definition</i>
--------------------------------	---

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

```
locusdef.rn4.exon
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:51:59 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

locusdef.rn4.intron *locusdef.rn4.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

```
locusdef.rn4.intron
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, rn4.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

For the rn4 genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:52:00 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

`locusdef.rn4.nearest_gene`*locusdef.rn4.nearest_gene locus definition*

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage`locusdef.rn4.nearest_gene`**Format**

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the `rn4` genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:51:58 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2` and `org.Rn.eg.db_3.5.0`.

`locusdef.rn4.nearest_tss`*locusdef.rn4.nearest_tss locus definition*

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.rn4.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn4`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

For the `rn4` genome, original gene IDs are from ENSEMBL and so an additional step of converting to Entrez IDs is done.

Built on Fri Apr 13 09:51:58 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2` and `org.Rn.eg.db_3.5.0`.

```
locusdef.rn5.10kb      locusdef.rn5.10kb locus definition
```

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

```
locusdef.rn5.10kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:20 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.10kb_outside

locusdef.rn5.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn5.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:21 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.10kb_outside_upstream
locusdef.rn5.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.rn5.10kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:21 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.1kb *locusdef.rn5.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

locusdef.rn5.1kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:19 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2` and `org.Rn.eg.db_3.5.0`.

locusdef.rn5.1kb_outside

locusdef.rn5.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn5.1kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:19 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.1kb_outside_upstream
locusdef.rn5.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn5.1kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:19 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.5kb *locusdef.rn5.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.rn5.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:20 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.5kb_outside *locusdef.rn5.5kb_outside locus definition*

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn5.5kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:20 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2` and `org.Rn.eg.db_3.5.0`.

locusdef.rn5.5kb_outside_upstream

locusdef.rn5.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn5.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:20 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.exon *locusdef.rn5.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.rn5.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn5.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:17 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.intron *locusdef.rn5.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.rn5.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:19 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2` and `org.Rn.eg.db_3.5.0`.

`locusdef.rn5.nearest_gene`

locusdef.rn5.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

`locusdef.rn5.nearest_gene`

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:16 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn5.nearest_tss
locusdef.rn5.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.rn5.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn5`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:16 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

locusdef.rn6.10kb *locusdef.rn6.10kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 10kb upstream and downstream of the TSS.

Usage

locusdef.rn6.10kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:39 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.10kb_outside
locusdef.rn6.10kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn6.10kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn6`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:40 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1` and `org.Rn.eg.db_3.5.0`.

locusdef.rn6.10kb_outside_upstream

locusdef.rn6.10kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 10kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn6.10kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn6`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:39 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.1kb *locusdef.rn6.1kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 1kb upstream and downstream of the TSS.

Usage

```
locusdef.rn6.1kb
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn6`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:38 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.1kb_outside
locusdef.rn6.1kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

locusdef.rn6.1kb_outside

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:38 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.1kb_outside_upstream
locusdef.rn6.1kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 1kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

locusdef.rn6.1kb_outside_upstream

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:38 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.5kb *locusdef.rn6.5kb locus definition*

Description

A LocusDefinition where a gene locus is defined within 5kb upstream and downstream of the TSS.

Usage

locusdef.rn6.5kb

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:38 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.5kb_outside

locusdef.rn6.5kb_outside locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream and downstream of the TSS and bounded by the midpoints between the TSS and the next upstream and downstream TSSs.

Usage

```
locusdef.rn6.5kb_outside
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn6`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:39 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1` and `org.Rn.eg.db_3.5.0`.

locusdef.rn6.5kb_outside_upstream

locusdef.rn6.5kb_outside_upstream locus definition

Description

A LocusDefinition where a gene locus is defined as the region beyond 5kb upstream of the TSS and bounded by the midpoint between the TSS and the next upstream TSS.

Usage

```
locusdef.rn6.5kb_outside_upstream
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:39 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.exon *locusdef.rn6.exon locus definition*

Description

A LocusDefinition where a gene locus is defined as the exons belonging to genes.

Usage

locusdef.rn6.exon

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:36 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.intron *locusdef.rn6.intron locus definition*

Description

A LocusDefinition where a gene locus is defined as the introns belonging to genes.

Usage

locusdef.rn6.intron

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID gene_id and gene symbol symbol

dframe A data.frame of the locus definitions with columns for chr, start, end, gene_id, and symbol

genome.build A character indicating the genome build. In this case, rn6.

organism A character indicating the organism name. In this case, Rattus norvegicus.

Details

Built on Fri Apr 13 09:52:37 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

locusdef.rn6.nearest_gene
locusdef.rn6.nearest_gene locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs and TESs.

Usage

locusdef.rn6.nearest_gene

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn6`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:35 2018.

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1` and `org.Rn.eg.db_3.5.0`.

locusdef.rn6.nearest_tss

locusdef.rn6.nearest_tss locus definition

Description

A LocusDefinition where a gene locus is defined as the region spanning the midpoints between adjacent TSSs.

Usage

```
locusdef.rn6.nearest_tss
```

Format

A LocusDefinition object with the following slots:

granges A GRanges of the locus definitions with mcols for Entrez Gene ID `gene_id` and gene symbol `symbol`

dframe A data.frame of the locus definitions with columns for `chr`, `start`, `end`, `gene_id`, and `symbol`

genome.build A character indicating the genome build. In this case, `rn6`.

organism A character indicating the organism name. In this case, `Rattus norvegicus`.

Details

Built on Fri Apr 13 09:52:34 2018.

Source

R packages: TxDb.Rnorvegicus.UCSC.m6.refGene_3.4.1 and org.Rn.eg.db_3.5.0.

LocusDefinition-class *Class "LocusDefinition"*

Description

A storage class representing gene locus definitions and their corresponding metadata.

Objects from the Class

Objects can be created by calls of the form `new("LocusDefinition")`. These objects are used internally by the `chipenrich` package and users will not likely need to create these.

Slots

`dframe`: Object of class "data.frame". Each row represents a locus for a particular geneid.
`granges`: Object of class "GenomicRanges". Locus definitions stored as a GenomicRanges object.
`genome.build`: Object of class "character". Genome build these definitions were generated from.
`organism`: Object of class "character". Organism code.

Note

Not typically accessed by the user - this is used internally by the `chipenrich` package.

Author(s)

Ryan Welch <welchr@umich.edu>

Examples

```
# Show info about the class.
showClass("LocusDefinition");

# Example of what a locus definition object looks like.
data(locusdef.mm9.nearest_tss)
lapply(attributes(locusdef.mm9.nearest_tss), head)
```

mappa.hg19.10kb.100mer

mappa.hg19.10kb.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.24mer *mappa.hg19.10kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.36mer *mappa.hg19.10kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 36mer

These objects are used internally by the *chipenrich* package.

Usage

```
data(mappa.hg19.10kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.40mer *mappa.hg19.10kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.50mer *mappa.hg19.10kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.10kb.75mer *mappa.hg19.10kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 10kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.10kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.1kb.100mer *mappa.hg19.1kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.1kb.24mer *mappa.hg19.1kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.1kb.36mer *mappa.hg19.1kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.40mer` *mappa.hg19.1kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.1kb.50mer` *mappa.hg19.1kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.1kb.75mer *mappa.hg19.1kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 1kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.1kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.100mer *mappa.hg19.5kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.24mer *mappa.hg19.5kb.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.36mer *mappa.hg19.5kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.40mer *mappa.hg19.5kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.50mer *mappa.hg19.5kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.5kb.75mer *mappa.hg19.5kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: 5kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.5kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.100mer

mappa.hg19.exon.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.24mer *mappa.hg19.exon.24mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.36mer *mappa.hg19.exon.36mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.40mer *mappa.hg19.exon.40mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.50mer *mappa.hg19.exon.50mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.exon.75mer *mappa.hg19.exon.75mer*

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: exon
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.exon.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.100mer

mappa.hg19.intron.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.24mer

mappa.hg19.intron.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.36mer

mappa.hg19.intron.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.40mer

mappa.hg19.intron.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.50mer

mappa.hg19.intron.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.intron.75mer

mappa.hg19.intron.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: intron
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.intron.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_gene.100mer`
mappa.hg19.nearest_gene.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 100mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_gene.100mer)
```

Format

A data frame containing:

`geneid` Entrez Gene IDs

`mappa` Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.hg19.nearest_gene.24mer`
mappa.hg19.nearest_gene.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 24mer

These objects are used internally by the `chipenrich` package.

Usage

```
data(mappa.hg19.nearest_gene.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_gene.36mer

mappa.hg19.nearest_gene.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_gene.40mer
mappa.hg19.nearest_gene.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_gene.50mer
mappa.hg19.nearest_gene.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_gene.75mer

mappa.hg19.nearest_gene.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_gene
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_gene.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.100mer
mappa.hg19.nearest_tss.100mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.24mer
mappa.hg19.nearest_tss.24mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 24mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.24mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.36mer

mappa.hg19.nearest_tss.36mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.40mer
mappa.hg19.nearest_tss.40mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.50mer
mappa.hg19.nearest_tss.50mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.hg19.nearest_tss.75mer

mappa.hg19.nearest_tss.75mer

Description

Gene locus mappability data, calculated for:

- Build: hg19
- Locus definition: nearest_tss
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.hg19.nearest_tss.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.100mer *mappa.mm9.10kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.10kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.36mer *mappa.mm9.10kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.10kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.40mer *mappa.mm9.10kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.10kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.50mer *mappa.mm9.10kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.10kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.10kb.75mer *mappa.mm9.10kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 10kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.1kb.100mer` *mappa.mm9.1kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.1kb.36mer *mappa.mm9.1kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.1kb.40mer *mappa.mm9.1kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.1kb.50mer *mappa.mm9.1kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.1kb.75mer *mappa.mm9.1kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 1kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.1kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.100mer *mappa.mm9.5kb.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.5kb.36mer` *mappa.mm9.5kb.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.40mer *mappa.mm9.5kb.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.50mer *mappa.mm9.5kb.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.5kb.75mer *mappa.mm9.5kb.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: 5kb
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.5kb.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.100mer *mappa.mm9.exon.100mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.36mer *mappa.mm9.exon.36mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.40mer *mappa.mm9.exon.40mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.50mer *mappa.mm9.exon.50mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.exon.75mer *mappa.mm9.exon.75mer*

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: exon
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.exon.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

`mappa.mm9.intron.100mer`

mappa.mm9.intron.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.intron.36mer

mappa.mm9.intron.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.intron.40mer

mappa.mm9.intron.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.intron.50mer

mappa.mm9.intron.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.intron.75mer

mappa.mm9.intron.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: intron
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.intron.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.100mer

mappa.mm9.nearest_gene.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.36mer

mappa.mm9.nearest_gene.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.40mer
mappa.mm9.nearest_gene.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.50mer
mappa.mm9.nearest_gene.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_gene.75mer

mappa.mm9.nearest_gene.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_gene
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_gene.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.100mer
mappa.mm9.nearest_tss.100mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 100mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.100mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.36mer
mappa.mm9.nearest_tss.36mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 36mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.36mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.40mer

mappa.mm9.nearest_tss.40mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 40mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.40mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.50mer
mappa.mm9.nearest_tss.50mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 50mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.50mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs
mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

mappa.mm9.nearest_tss.75mer
mappa.mm9.nearest_tss.75mer

Description

Gene locus mappability data, calculated for:

- Build: mm9
- Locus definition: nearest_tss
- K-Mer Reads: 75mer

These objects are used internally by the chipenrich package.

Usage

```
data(mappa.mm9.nearest_tss.75mer)
```

Format

A data frame containing:

geneid Entrez Gene IDs

mappa Gene locus mappability

Author(s)

Ryan Welch <welchr@umich.edu>

See Also

For more information about gene locus definitions: [chipenrich.data](#)

peaks_E2F4

ChIP-seq Peaks for the E2F4 Transcription Factor

Description

A dataset containing the binding locations (peaks) of the transcription factor E2F4 called from a ChIP-seq experiment

Usage

```
peaks_E2F4
```

Format

A data frame containing 16,245 peak binding locations. Each row is a peak location, and the 3 variables/columns are chromosome, start peak coordinate, and end peak coordinate. Peak coordinates are in hg19 (UCSC) coordinates.

Source

The data and information regarding the experiment can be found in the following publication:

Lee, B. K., A. A. Bhinge, et al. (2011). "Wide-ranging functions of E2F4 in transcriptional activation and repression revealed by genome-wide analysis." *Nucleic Acids Res* 39(9): 3558-3573.

Examples

```
# Load E2F4 peak data.
data(peaks_E2F4)

# Print the first 10 peaks in the dataset.
print(head(peaks_E2F4))
```

peaks_H3K4me3_GM12878 *ChIP-seq Peaks for the Histone Modification H3K4me3 in GM12878*

Description

A dataset containing the binding locations (peaks) of the histone modification H3K4me3 called from a ChIP-seq experiment in the GM12878 cell line

Usage

```
peaks_H3K4me3_GM12878
```

Format

A data frame containing 57,476 peak binding locations. Each row is a peak location, and the 3 variables/columns are chromosome, start peak coordinate, and end peak coordinate. Peak coordinates are in hg19 (UCSC) coordinates.

Source

The data and information regarding the experiment can be found at the following ENCODE URL:

<http://hgdownload.cse.ucsc.edu/goldenPath/hg19/encodeDCC/wgEncodeBroadHistone/wgEncodeBroadHistoneGm12878H>

Examples

```
# Load H3K4me3 in GM12878 peak data.
data(peaks_H3K4me3_GM12878)

# Print the first 10 peaks in the dataset.
print(head(peaks_H3K4me3_GM12878))
```

```
spline.log_dtss.90ENCODE
```

DTSS Spline adjustment

Description

A `mgcv::gam` object on a combined data of 90 ENCODE ChIP-seq datasets that modeled the relationship between a gene's locus length the distance from a peak to the gene's transcription start site, using a cubic spline. This is used to adjust for the proximity to TSSes test.

Usage

```
spline.log_dtss.90ENCODE
```

Format

An object of class `gam` (inherits from `glm`, `lm`) of length 46.

tss.danRer10	<i>tss.danRer10 TSS locations</i>
--------------	-----------------------------------

Description

A GRanges with all the TSSs for danRer10. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.danRer10
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Drerio.UCSC.danRer10.refGene_3.4.2 and org.Dr.eg.db_3.5.0.

tss.dm3	<i>tss.dm3 TSS locations</i>
---------	------------------------------

Description

A GRanges with all the TSSs for dm3. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.dm3
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Dmelanogaster.UCSC.dm3.ensGene_3.2.2 and org.Dm.eg.db_3.5.0.

`tss.dm6`*tss.dm6 TSS locations*

Description

A GRanges with all the TSSs for dm6. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage`tss.dm6`**Format**

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Dmelanogaster.UCSC.dm6.ensGene_3.4.1 and org.Dm.eg.db_3.5.0.

`tss.hg19`*tss.hg19 TSS locations*

Description

A GRanges with all the TSSs for hg19. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage`tss.hg19`**Format**

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Hsapiens.UCSC.hg19.knownGene_3.2.2 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.annotation and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/GRCh37_mapping/gencode.v25lift37.metadata. EntrezG

tss.hg38

tss.hg38 TSS locations

Description

A GRanges with all the TSSs for hg38. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.hg38
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Hsapiens.UCSC.hg38.knownGene_3.4.0 and org.Hs.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_human/release_25/gencode.v25.metadata. EntrezGene.gz

tss.mm10

tss.mm10 TSS locations

Description

A GRanges with all the TSSs for mm10. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.mm10
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Mmusculus.UCSC.mm10.knownGene_3.4.0 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M12/gencode.vM12.metadata.EntrezGene.gz

tss.mm9

tss.mm9 TSS locations

Description

A GRanges with all the TSSs for mm9. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

tss.mm9

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Mmusculus.UCSC.mm9.knownGene_3.2.2 and org.Mm.eg.db_3.5.0. GENCODE resources: ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.annotation.gff3.gz and ftp://ftp.sanger.ac.uk/pub/gencode/Gencode_mouse/release_M9/gencode.vM9.metadata.EntrezGene.gz

tss.rn4	<i>tss.rn4 TSS locations</i>
---------	------------------------------

Description

A GRanges with all the TSSs for rn4. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.rn4
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Rnorvegicus.UCSC.rn4.ensGene_3.2.2 and org.Rn.eg.db_3.5.0.

tss.rn5	<i>tss.rn5 TSS locations</i>
---------	------------------------------

Description

A GRanges with all the TSSs for rn5. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.rn5
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: TxDb.Rnorvegicus.UCSC.rn5.refGene_3.4.2 and org.Rn.eg.db_3.5.0.

tss.rn6	<i>tss.rn6 TSS locations</i>
---------	------------------------------

Description

A GRanges with all the TSSs for rn6. Primarily used in the `assign_peaks()` function to report distance of a peak to the nearest TSS. Also used to build the QC plot with distribution of peaks to TSSs.

Usage

```
tss.rn6
```

Format

A GRanges object with the following mcols:

gene_id The Entrez ID for the TSS

symbol The gene symbol for the TSS

Source

R packages: `TxDb.Rnorvegicus.UCSC.rn6.refGene_3.4.1` and `org.Rn.eg.db_3.5.0`.

Index

* classes

GeneSet-class, [9](#)

LocusDefinition-class, [139](#)

* datasets

enhancer.dnase_thurman.0, [8](#)

gene.enh.desc, [9](#)

geneset.biocarta_pathway.hsa, [10](#)

geneset.biocarta_pathway.mmu, [11](#)

geneset.biocarta_pathway.rno, [11](#)

geneset.ctd.hsa, [12](#)

geneset.ctd.mmu, [12](#)

geneset.cytoband.hsa, [13](#)

geneset.drug_bank.hsa, [14](#)

geneset.drug_bank.mmu, [14](#)

geneset.drug_bank.rno, [15](#)

geneset.GOBP.dme, [15](#)

geneset.GOBP.dre, [16](#)

geneset.GOBP.hsa, [17](#)

geneset.GOBP.mmu, [17](#)

geneset.GOBP.rno, [18](#)

geneset.GOCC.dme, [19](#)

geneset.GOCC.dre, [19](#)

geneset.GOCC.hsa, [20](#)

geneset.GOCC.mmu, [21](#)

geneset.GOCC.rno, [21](#)

geneset.GOMF.dme, [22](#)

geneset.GOMF.dre, [23](#)

geneset.GOMF.hsa, [23](#)

geneset.GOMF.mmu, [24](#)

geneset.GOMF.rno, [25](#)

geneset.hallmark.hsa, [25](#)

geneset.immunologic.hsa, [26](#)

geneset.kegg_pathway.hsa, [27](#)

geneset.kegg_pathway.mmu, [28](#)

geneset.kegg_pathway.rno, [28](#)

geneset.mesh.hsa, [29](#)

geneset.mesh.mmu, [29](#)

geneset.mesh.rno, [30](#)

geneset.metabolite.hsa, [30](#)

geneset.metabolite.mmu, [31](#)

geneset.metabolite.rno, [31](#)

geneset.micrna.hsa, [32](#)

geneset.oncogenic.hsa, [32](#)

geneset.panther_pathway.hsa, [33](#)

geneset.panther_pathway.mmu, [34](#)

geneset.panther_pathway.rno, [34](#)

geneset.pfam.hsa, [35](#)

geneset.pfam.mmu, [35](#)

geneset.pfam.rno, [36](#)

geneset.protein_interaction_biogrid.hsa, [36](#)

geneset.reactome.dme, [37](#)

geneset.reactome.dre, [38](#)

geneset.reactome.hsa, [38](#)

geneset.reactome.mmu, [39](#)

geneset.reactome.rno, [40](#)

geneset.transcription_factors.hsa, [41](#)

geneset.transcription_factors.mmu, [41](#)

geneset.transcription_factors.rno, [42](#)

locusdef.danRer10.10kb, [42](#)

locusdef.danRer10.10kb_outside, [43](#)

locusdef.danRer10.10kb_outside_upstream, [44](#)

locusdef.danRer10.1kb, [45](#)

locusdef.danRer10.1kb_outside, [45](#)

locusdef.danRer10.1kb_outside_upstream, [46](#)

locusdef.danRer10.5kb, [47](#)

locusdef.danRer10.5kb_outside, [48](#)

locusdef.danRer10.5kb_outside_upstream, [48](#)

locusdef.danRer10.exon, [49](#)

locusdef.danRer10.intron, [50](#)

locusdef.danRer10.nearest_gene, [50](#)

locusdef.danRer10.nearest_tss, [51](#)

- locusdef.dm3.10kb, [52](#)
- locusdef.dm3.10kb_outside, [53](#)
- locusdef.dm3.10kb_outside_upstream, [53](#)
- locusdef.dm3.1kb, [54](#)
- locusdef.dm3.1kb_outside, [55](#)
- locusdef.dm3.1kb_outside_upstream, [56](#)
- locusdef.dm3.5kb, [56](#)
- locusdef.dm3.5kb_outside, [57](#)
- locusdef.dm3.5kb_outside_upstream, [58](#)
- locusdef.dm3.exon, [59](#)
- locusdef.dm3.intron, [59](#)
- locusdef.dm3.nearest_gene, [60](#)
- locusdef.dm3.nearest_tss, [61](#)
- locusdef.dm6.10kb, [62](#)
- locusdef.dm6.10kb_outside, [62](#)
- locusdef.dm6.10kb_outside_upstream, [63](#)
- locusdef.dm6.1kb, [64](#)
- locusdef.dm6.1kb_outside, [65](#)
- locusdef.dm6.1kb_outside_upstream, [65](#)
- locusdef.dm6.5kb, [66](#)
- locusdef.dm6.5kb_outside, [67](#)
- locusdef.dm6.5kb_outside_upstream, [68](#)
- locusdef.dm6.exon, [68](#)
- locusdef.dm6.intron, [69](#)
- locusdef.dm6.nearest_gene, [70](#)
- locusdef.dm6.nearest_tss, [71](#)
- locusdef.hg19.10kb, [71](#)
- locusdef.hg19.10kb_outside, [72](#)
- locusdef.hg19.10kb_outside_upstream, [73](#)
- locusdef.hg19.1kb, [74](#)
- locusdef.hg19.1kb_outside, [74](#)
- locusdef.hg19.1kb_outside_upstream, [75](#)
- locusdef.hg19.5kb, [76](#)
- locusdef.hg19.5kb_outside, [77](#)
- locusdef.hg19.5kb_outside_upstream, [77](#)
- locusdef.hg19.exon, [78](#)
- locusdef.hg19.intron, [79](#)
- locusdef.hg19.nearest_gene, [80](#)
- locusdef.hg19.nearest_tss, [80](#)
- locusdef.hg38.10kb, [81](#)
- locusdef.hg38.10kb_outside, [82](#)
- locusdef.hg38.10kb_outside_upstream, [83](#)
- locusdef.hg38.1kb, [83](#)
- locusdef.hg38.1kb_outside, [84](#)
- locusdef.hg38.1kb_outside_upstream, [85](#)
- locusdef.hg38.5kb, [86](#)
- locusdef.hg38.5kb_outside, [86](#)
- locusdef.hg38.5kb_outside_upstream, [87](#)
- locusdef.hg38.exon, [88](#)
- locusdef.hg38.intron, [89](#)
- locusdef.hg38.nearest_gene, [89](#)
- locusdef.hg38.nearest_tss, [90](#)
- locusdef.mm10.10kb, [91](#)
- locusdef.mm10.10kb_outside, [92](#)
- locusdef.mm10.10kb_outside_upstream, [92](#)
- locusdef.mm10.1kb, [93](#)
- locusdef.mm10.1kb_outside, [94](#)
- locusdef.mm10.1kb_outside_upstream, [95](#)
- locusdef.mm10.5kb, [95](#)
- locusdef.mm10.5kb_outside, [96](#)
- locusdef.mm10.5kb_outside_upstream, [97](#)
- locusdef.mm10.exon, [98](#)
- locusdef.mm10.intron, [98](#)
- locusdef.mm10.nearest_gene, [99](#)
- locusdef.mm10.nearest_tss, [100](#)
- locusdef.mm9.10kb, [101](#)
- locusdef.mm9.10kb_outside, [101](#)
- locusdef.mm9.10kb_outside_upstream, [102](#)
- locusdef.mm9.1kb, [103](#)
- locusdef.mm9.1kb_outside, [104](#)
- locusdef.mm9.1kb_outside_upstream, [104](#)
- locusdef.mm9.5kb, [105](#)
- locusdef.mm9.5kb_outside, [106](#)
- locusdef.mm9.5kb_outside_upstream, [107](#)
- locusdef.mm9.exon, [107](#)
- locusdef.mm9.intron, [108](#)
- locusdef.mm9.nearest_gene, [109](#)
- locusdef.mm9.nearest_tss, [110](#)

- locusdef.rn4.10kb, [110](#)
- locusdef.rn4.10kb_outside, [111](#)
- locusdef.rn4.10kb_outside_upstream, [112](#)
- locusdef.rn4.1kb, [113](#)
- locusdef.rn4.1kb_outside, [113](#)
- locusdef.rn4.1kb_outside_upstream, [114](#)
- locusdef.rn4.5kb, [115](#)
- locusdef.rn4.5kb_outside, [116](#)
- locusdef.rn4.5kb_outside_upstream, [116](#)
- locusdef.rn4.exon, [117](#)
- locusdef.rn4.intron, [118](#)
- locusdef.rn4.nearest_gene, [119](#)
- locusdef.rn4.nearest_tss, [119](#)
- locusdef.rn5.10kb, [120](#)
- locusdef.rn5.10kb_outside, [121](#)
- locusdef.rn5.10kb_outside_upstream, [122](#)
- locusdef.rn5.1kb, [122](#)
- locusdef.rn5.1kb_outside, [123](#)
- locusdef.rn5.1kb_outside_upstream, [124](#)
- locusdef.rn5.5kb, [125](#)
- locusdef.rn5.5kb_outside, [125](#)
- locusdef.rn5.5kb_outside_upstream, [126](#)
- locusdef.rn5.exon, [127](#)
- locusdef.rn5.intron, [127](#)
- locusdef.rn5.nearest_gene, [128](#)
- locusdef.rn5.nearest_tss, [129](#)
- locusdef.rn6.10kb, [130](#)
- locusdef.rn6.10kb_outside, [130](#)
- locusdef.rn6.10kb_outside_upstream, [131](#)
- locusdef.rn6.1kb, [132](#)
- locusdef.rn6.1kb_outside, [133](#)
- locusdef.rn6.1kb_outside_upstream, [133](#)
- locusdef.rn6.5kb, [134](#)
- locusdef.rn6.5kb_outside, [135](#)
- locusdef.rn6.5kb_outside_upstream, [135](#)
- locusdef.rn6.exon, [136](#)
- locusdef.rn6.intron, [137](#)
- locusdef.rn6.nearest_gene, [137](#)
- locusdef.rn6.nearest_tss, [138](#)
- mappa.hg19.10kb.100mer, [140](#)
- mappa.hg19.10kb.24mer, [140](#)
- mappa.hg19.10kb.36mer, [141](#)
- mappa.hg19.10kb.40mer, [142](#)
- mappa.hg19.10kb.50mer, [142](#)
- mappa.hg19.10kb.75mer, [143](#)
- mappa.hg19.1kb.100mer, [144](#)
- mappa.hg19.1kb.24mer, [144](#)
- mappa.hg19.1kb.36mer, [145](#)
- mappa.hg19.1kb.40mer, [146](#)
- mappa.hg19.1kb.50mer, [146](#)
- mappa.hg19.1kb.75mer, [147](#)
- mappa.hg19.5kb.100mer, [148](#)
- mappa.hg19.5kb.24mer, [148](#)
- mappa.hg19.5kb.36mer, [149](#)
- mappa.hg19.5kb.40mer, [150](#)
- mappa.hg19.5kb.50mer, [150](#)
- mappa.hg19.5kb.75mer, [151](#)
- mappa.hg19.exon.100mer, [152](#)
- mappa.hg19.exon.24mer, [152](#)
- mappa.hg19.exon.36mer, [153](#)
- mappa.hg19.exon.40mer, [154](#)
- mappa.hg19.exon.50mer, [154](#)
- mappa.hg19.exon.75mer, [155](#)
- mappa.hg19.intron.100mer, [156](#)
- mappa.hg19.intron.24mer, [156](#)
- mappa.hg19.intron.36mer, [157](#)
- mappa.hg19.intron.40mer, [158](#)
- mappa.hg19.intron.50mer, [158](#)
- mappa.hg19.intron.75mer, [159](#)
- mappa.hg19.nearest_gene.100mer, [160](#)
- mappa.hg19.nearest_gene.24mer, [160](#)
- mappa.hg19.nearest_gene.36mer, [161](#)
- mappa.hg19.nearest_gene.40mer, [162](#)
- mappa.hg19.nearest_gene.50mer, [162](#)
- mappa.hg19.nearest_gene.75mer, [163](#)
- mappa.hg19.nearest_tss.100mer, [164](#)
- mappa.hg19.nearest_tss.24mer, [164](#)
- mappa.hg19.nearest_tss.36mer, [165](#)
- mappa.hg19.nearest_tss.40mer, [166](#)
- mappa.hg19.nearest_tss.50mer, [166](#)
- mappa.hg19.nearest_tss.75mer, [167](#)
- mappa.mm9.10kb.100mer, [168](#)
- mappa.mm9.10kb.36mer, [168](#)
- mappa.mm9.10kb.40mer, [169](#)
- mappa.mm9.10kb.50mer, [170](#)
- mappa.mm9.10kb.75mer, [170](#)

- mappa.mm9.1kb.100mer, [171](#)
 - mappa.mm9.1kb.36mer, [172](#)
 - mappa.mm9.1kb.40mer, [172](#)
 - mappa.mm9.1kb.50mer, [173](#)
 - mappa.mm9.1kb.75mer, [174](#)
 - mappa.mm9.5kb.100mer, [174](#)
 - mappa.mm9.5kb.36mer, [175](#)
 - mappa.mm9.5kb.40mer, [176](#)
 - mappa.mm9.5kb.50mer, [176](#)
 - mappa.mm9.5kb.75mer, [177](#)
 - mappa.mm9.exon.100mer, [178](#)
 - mappa.mm9.exon.36mer, [178](#)
 - mappa.mm9.exon.40mer, [179](#)
 - mappa.mm9.exon.50mer, [180](#)
 - mappa.mm9.exon.75mer, [180](#)
 - mappa.mm9.intron.100mer, [181](#)
 - mappa.mm9.intron.36mer, [182](#)
 - mappa.mm9.intron.40mer, [182](#)
 - mappa.mm9.intron.50mer, [183](#)
 - mappa.mm9.intron.75mer, [184](#)
 - mappa.mm9.nearest_gene.100mer, [184](#)
 - mappa.mm9.nearest_gene.36mer, [185](#)
 - mappa.mm9.nearest_gene.40mer, [186](#)
 - mappa.mm9.nearest_gene.50mer, [186](#)
 - mappa.mm9.nearest_gene.75mer, [187](#)
 - mappa.mm9.nearest_tss.100mer, [188](#)
 - mappa.mm9.nearest_tss.36mer, [188](#)
 - mappa.mm9.nearest_tss.40mer, [189](#)
 - mappa.mm9.nearest_tss.50mer, [190](#)
 - mappa.mm9.nearest_tss.75mer, [190](#)
 - peaks_E2F4, [191](#)
 - peaks_H3K4me3_GM12878, [192](#)
 - spline.log_dtss.90ENCODE, [192](#)
 - tss.danRer10, [193](#)
 - tss.dm3, [193](#)
 - tss.dm6, [194](#)
 - tss.hg19, [194](#)
 - tss.hg38, [195](#)
 - tss.mm10, [195](#)
 - tss.mm9, [196](#)
 - tss.rn4, [197](#)
 - tss.rn5, [197](#)
 - tss.rn6, [198](#)
- chipenrich.data, [8](#), [11](#), [13](#), [15](#), [28–31](#), [33](#),
[34](#), [36](#), [42](#), [140–191](#)
- chipenrich.data-package
 (chipenrich.data), [8](#)
- enhancer.dnase_thurman.0, [8](#)
 - gene.enh.desc, [9](#)
 - GeneSet-class, [9](#)
 - geneset.biocarta_pathway.hsa, [10](#)
 - geneset.biocarta_pathway.mmu, [11](#)
 - geneset.biocarta_pathway.rno, [11](#)
 - geneset.ctd.hsa, [12](#)
 - geneset.ctd.mmu, [12](#)
 - geneset.cytoband.hsa, [13](#)
 - geneset.drug_bank.hsa, [14](#)
 - geneset.drug_bank.mmu, [14](#)
 - geneset.drug_bank.rno, [15](#)
 - geneset.GOBP.dme, [15](#)
 - geneset.GOBP.dre, [16](#)
 - geneset.GOBP.hsa, [17](#)
 - geneset.GOBP.mmu, [17](#)
 - geneset.GOBP.rno, [18](#)
 - geneset.GOCC.dme, [19](#)
 - geneset.GOCC.dre, [19](#)
 - geneset.GOCC.hsa, [20](#)
 - geneset.GOCC.mmu, [21](#)
 - geneset.GOCC.rno, [21](#)
 - geneset.GOMF.dme, [22](#)
 - geneset.GOMF.dre, [23](#)
 - geneset.GOMF.hsa, [23](#)
 - geneset.GOMF.mmu, [24](#)
 - geneset.GOMF.rno, [25](#)
 - geneset.hallmark.hsa, [25](#)
 - geneset.immunologic.hsa, [26](#)
 - geneset.kegg_pathway.hsa, [27](#)
 - geneset.kegg_pathway.mmu, [28](#)
 - geneset.kegg_pathway.rno, [28](#)
 - geneset.mesh.hsa, [29](#)
 - geneset.mesh.mmu, [29](#)
 - geneset.mesh.rno, [30](#)
 - geneset.metabolite.hsa, [30](#)
 - geneset.metabolite.mmu, [31](#)
 - geneset.metabolite.rno, [31](#)
 - geneset.microrna.hsa, [32](#)
 - geneset.oncogenic.hsa, [32](#)
 - geneset.panther_pathway.hsa, [33](#)
 - geneset.panther_pathway.mmu, [34](#)
 - geneset.panther_pathway.rno, [34](#)
 - geneset.pfam.hsa, [35](#)
 - geneset.pfam.mmu, [35](#)
 - geneset.pfam.rno, [36](#)
 - geneset.protein_interaction_biogrid.hsa,
[36](#)

geneset.reactome.dme, 37
geneset.reactome.dre, 38
geneset.reactome.hsa, 38
geneset.reactome.mmu, 39
geneset.reactome.rno, 40
geneset.transcription_factors.hsa, 41
geneset.transcription_factors.mmu, 41
geneset.transcription_factors.rno, 42

locusdef.danRer10.10kb, 42
locusdef.danRer10.10kb_outside, 43
locusdef.danRer10.10kb_outside_upstream, 44
locusdef.danRer10.1kb, 45
locusdef.danRer10.1kb_outside, 45
locusdef.danRer10.1kb_outside_upstream, 46
locusdef.danRer10.5kb, 47
locusdef.danRer10.5kb_outside, 48
locusdef.danRer10.5kb_outside_upstream, 48
locusdef.danRer10.exon, 49
locusdef.danRer10.intron, 50
locusdef.danRer10.nearest_gene, 50
locusdef.danRer10.nearest_tss, 51
locusdef.dm3.10kb, 52
locusdef.dm3.10kb_outside, 53
locusdef.dm3.10kb_outside_upstream, 53
locusdef.dm3.1kb, 54
locusdef.dm3.1kb_outside, 55
locusdef.dm3.1kb_outside_upstream, 56
locusdef.dm3.5kb, 56
locusdef.dm3.5kb_outside, 57
locusdef.dm3.5kb_outside_upstream, 58
locusdef.dm3.exon, 59
locusdef.dm3.intron, 59
locusdef.dm3.nearest_gene, 60
locusdef.dm3.nearest_tss, 61
locusdef.dm6.10kb, 62
locusdef.dm6.10kb_outside, 62
locusdef.dm6.10kb_outside_upstream, 63
locusdef.dm6.1kb, 64
locusdef.dm6.1kb_outside, 65
locusdef.dm6.1kb_outside_upstream, 65
locusdef.dm6.5kb, 66
locusdef.dm6.5kb_outside, 67
locusdef.dm6.5kb_outside_upstream, 68
locusdef.dm6.exon, 68
locusdef.dm6.intron, 69
locusdef.dm6.nearest_gene, 70
locusdef.dm6.nearest_tss, 71
locusdef.hg19.10kb, 71
locusdef.hg19.10kb_outside, 72
locusdef.hg19.10kb_outside_upstream, 73
locusdef.hg19.1kb, 74
locusdef.hg19.1kb_outside, 74
locusdef.hg19.1kb_outside_upstream, 75
locusdef.hg19.5kb, 76
locusdef.hg19.5kb_outside, 77
locusdef.hg19.5kb_outside_upstream, 77
locusdef.hg19.exon, 78
locusdef.hg19.intron, 79
locusdef.hg19.nearest_gene, 80
locusdef.hg19.nearest_tss, 80
locusdef.hg38.10kb, 81
locusdef.hg38.10kb_outside, 82
locusdef.hg38.10kb_outside_upstream, 83
locusdef.hg38.1kb, 83
locusdef.hg38.1kb_outside, 84
locusdef.hg38.1kb_outside_upstream, 85
locusdef.hg38.5kb, 86
locusdef.hg38.5kb_outside, 86
locusdef.hg38.5kb_outside_upstream, 87
locusdef.hg38.exon, 88
locusdef.hg38.intron, 89
locusdef.hg38.nearest_gene, 89
locusdef.hg38.nearest_tss, 90
locusdef.mm10.10kb, 91
locusdef.mm10.10kb_outside, 92
locusdef.mm10.10kb_outside_upstream, 92
locusdef.mm10.1kb, 93
locusdef.mm10.1kb_outside, 94
locusdef.mm10.1kb_outside_upstream, 95
locusdef.mm10.5kb, 95
locusdef.mm10.5kb_outside, 96
locusdef.mm10.5kb_outside_upstream, 97
locusdef.mm10.exon, 98
locusdef.mm10.intron, 98
locusdef.mm10.nearest_gene, 99
locusdef.mm10.nearest_tss, 100
locusdef.mm9.10kb, 101
locusdef.mm9.10kb_outside, 101
locusdef.mm9.10kb_outside_upstream, 102

- locusdef.mm9.1kb, [103](#)
- locusdef.mm9.1kb_outside, [104](#)
- locusdef.mm9.1kb_outside_upstream, [104](#)
- locusdef.mm9.5kb, [105](#)
- locusdef.mm9.5kb_outside, [106](#)
- locusdef.mm9.5kb_outside_upstream, [107](#)
- locusdef.mm9.exon, [107](#)
- locusdef.mm9.intron, [108](#)
- locusdef.mm9.nearest_gene, [109](#)
- locusdef.mm9.nearest_tss, [110](#)
- locusdef.rn4.10kb, [110](#)
- locusdef.rn4.10kb_outside, [111](#)
- locusdef.rn4.10kb_outside_upstream, [112](#)
- locusdef.rn4.1kb, [113](#)
- locusdef.rn4.1kb_outside, [113](#)
- locusdef.rn4.1kb_outside_upstream, [114](#)
- locusdef.rn4.5kb, [115](#)
- locusdef.rn4.5kb_outside, [116](#)
- locusdef.rn4.5kb_outside_upstream, [116](#)
- locusdef.rn4.exon, [117](#)
- locusdef.rn4.intron, [118](#)
- locusdef.rn4.nearest_gene, [119](#)
- locusdef.rn4.nearest_tss, [119](#)
- locusdef.rn5.10kb, [120](#)
- locusdef.rn5.10kb_outside, [121](#)
- locusdef.rn5.10kb_outside_upstream, [122](#)
- locusdef.rn5.1kb, [122](#)
- locusdef.rn5.1kb_outside, [123](#)
- locusdef.rn5.1kb_outside_upstream, [124](#)
- locusdef.rn5.5kb, [125](#)
- locusdef.rn5.5kb_outside, [125](#)
- locusdef.rn5.5kb_outside_upstream, [126](#)
- locusdef.rn5.exon, [127](#)
- locusdef.rn5.intron, [127](#)
- locusdef.rn5.nearest_gene, [128](#)
- locusdef.rn5.nearest_tss, [129](#)
- locusdef.rn6.10kb, [130](#)
- locusdef.rn6.10kb_outside, [130](#)
- locusdef.rn6.10kb_outside_upstream, [131](#)
- locusdef.rn6.1kb, [132](#)
- locusdef.rn6.1kb_outside, [133](#)
- locusdef.rn6.1kb_outside_upstream, [133](#)
- locusdef.rn6.5kb, [134](#)
- locusdef.rn6.5kb_outside, [135](#)
- locusdef.rn6.5kb_outside_upstream, [135](#)
- locusdef.rn6.exon, [136](#)
- locusdef.rn6.intron, [137](#)
- locusdef.rn6.nearest_gene, [137](#)
- locusdef.rn6.nearest_tss, [138](#)
- LocusDefinition-class, [139](#)
- mappa.hg19.10kb.100mer, [140](#)
- mappa.hg19.10kb.24mer, [140](#)
- mappa.hg19.10kb.36mer, [141](#)
- mappa.hg19.10kb.40mer, [142](#)
- mappa.hg19.10kb.50mer, [142](#)
- mappa.hg19.10kb.75mer, [143](#)
- mappa.hg19.1kb.100mer, [144](#)
- mappa.hg19.1kb.24mer, [144](#)
- mappa.hg19.1kb.36mer, [145](#)
- mappa.hg19.1kb.40mer, [146](#)
- mappa.hg19.1kb.50mer, [146](#)
- mappa.hg19.1kb.75mer, [147](#)
- mappa.hg19.5kb.100mer, [148](#)
- mappa.hg19.5kb.24mer, [148](#)
- mappa.hg19.5kb.36mer, [149](#)
- mappa.hg19.5kb.40mer, [150](#)
- mappa.hg19.5kb.50mer, [150](#)
- mappa.hg19.5kb.75mer, [151](#)
- mappa.hg19.exon.100mer, [152](#)
- mappa.hg19.exon.24mer, [152](#)
- mappa.hg19.exon.36mer, [153](#)
- mappa.hg19.exon.40mer, [154](#)
- mappa.hg19.exon.50mer, [154](#)
- mappa.hg19.exon.75mer, [155](#)
- mappa.hg19.intron.100mer, [156](#)
- mappa.hg19.intron.24mer, [156](#)
- mappa.hg19.intron.36mer, [157](#)
- mappa.hg19.intron.40mer, [158](#)
- mappa.hg19.intron.50mer, [158](#)
- mappa.hg19.intron.75mer, [159](#)
- mappa.hg19.nearest_gene.100mer, [160](#)
- mappa.hg19.nearest_gene.24mer, [160](#)
- mappa.hg19.nearest_gene.36mer, [161](#)
- mappa.hg19.nearest_gene.40mer, [162](#)
- mappa.hg19.nearest_gene.50mer, [162](#)
- mappa.hg19.nearest_gene.75mer, [163](#)
- mappa.hg19.nearest_tss.100mer, [164](#)
- mappa.hg19.nearest_tss.24mer, [164](#)
- mappa.hg19.nearest_tss.36mer, [165](#)
- mappa.hg19.nearest_tss.40mer, [166](#)
- mappa.hg19.nearest_tss.50mer, [166](#)
- mappa.hg19.nearest_tss.75mer, [167](#)
- mappa.mm9.10kb.100mer, [168](#)

mappa.mm9.10kb.36mer, 168
mappa.mm9.10kb.40mer, 169
mappa.mm9.10kb.50mer, 170
mappa.mm9.10kb.75mer, 170
mappa.mm9.1kb.100mer, 171
mappa.mm9.1kb.36mer, 172
mappa.mm9.1kb.40mer, 172
mappa.mm9.1kb.50mer, 173
mappa.mm9.1kb.75mer, 174
mappa.mm9.5kb.100mer, 174
mappa.mm9.5kb.36mer, 175
mappa.mm9.5kb.40mer, 176
mappa.mm9.5kb.50mer, 176
mappa.mm9.5kb.75mer, 177
mappa.mm9.exon.100mer, 178
mappa.mm9.exon.36mer, 178
mappa.mm9.exon.40mer, 179
mappa.mm9.exon.50mer, 180
mappa.mm9.exon.75mer, 180
mappa.mm9.intron.100mer, 181
mappa.mm9.intron.36mer, 182
mappa.mm9.intron.40mer, 182
mappa.mm9.intron.50mer, 183
mappa.mm9.intron.75mer, 184
mappa.mm9.nearest_gene.100mer, 184
mappa.mm9.nearest_gene.36mer, 185
mappa.mm9.nearest_gene.40mer, 186
mappa.mm9.nearest_gene.50mer, 186
mappa.mm9.nearest_gene.75mer, 187
mappa.mm9.nearest_tss.100mer, 188
mappa.mm9.nearest_tss.36mer, 188
mappa.mm9.nearest_tss.40mer, 189
mappa.mm9.nearest_tss.50mer, 190
mappa.mm9.nearest_tss.75mer, 190

peaks_E2F4, 191
peaks_H3K4me3_GM12878, 192

spline.log_dtss.90ENCODE, 192

tss.danRer10, 193
tss.dm3, 193
tss.dm6, 194
tss.hg19, 194
tss.hg38, 195
tss.mm10, 195
tss.mm9, 196
tss.rn4, 197
tss.rn5, 197
tss.rn6, 198